

型号		SL135	SL180	SL225	SL450	SL675
参数						
最大额定钩载	kN(ton)	1350(135)	1800(180)	2250(225)	4500(450)	6750(675)
最大转速	rpm	300				
最大工作压力	MPa (psi)	35 (5000)				52(7500)
大钩间隙	MM	495	540	540	549	584
中心管直径	MM(in)	64(2-1/2) 64(2-1/2)		75(3) 75(3)		102(4)
接头螺纹	To Stem	4-1/2"REG LH	6-5/8"REG LH		7-5/8" REG LH	
	To Kelly	6-5/8" REG LH				
外形尺寸(长 X 宽 X 高)	MM	2505 x 758 x840	2786 x 706 x 791	2880 x 1046 x 1065	3015 x 1096 x 1065	3115 x 1143 x 990
重量	kg	1341	1834	2570	3060	4000
注：上述水龙头，分为带旋扣器和不带旋扣器两种。						

Model		SL135	SL170	SL225	SL450	SL675
Specifications						
Max. Hook Load Rating	kN(lbs)	1350 (300,000)	1700 (350,000)	2250 (500,000)	4500 (1,000,000)	6750 (1,500,000)
Max. Speed	rpm	300	300	300	300	300
Max. Working Pressure	Mpa( psi)	35 (5000)	35 (5000)	35 (5000)	35 (5000)	52(7500)
Hook Clearance over Gooseneck	mm(in)	495 (19 <sup>1</sup> / <sub>2</sub> )	540 (21 <sup>1</sup> / <sub>4</sub> )	540 (21 <sup>1</sup> / <sub>4</sub> )	549 (21 <sup>5</sup> / <sub>8</sub> )	584(23)
Dia. of Stem	mm/in	64 (2 <sup>1</sup> / <sub>2</sub> )	64 (2 <sup>1</sup> / <sub>2</sub> )	75 (3)	75 (3)	102(4)
Coupling Thread	To Stem	4 <sup>1</sup> / <sub>2</sub> REG LH	4 <sup>1</sup> / <sub>2</sub> REG LH	6 <sup>5</sup> / <sub>8</sub> REG LH	7 <sup>5</sup> / <sub>8</sub> REG LH	7-5/8" REG LH
	To Kelly	6 <sup>5</sup> / <sub>8</sub> REG LH	6 <sup>5</sup> / <sub>8</sub> REG LH	6 <sup>5</sup> / <sub>8</sub> REG LH	6 <sup>5</sup> / <sub>8</sub> REG LH	6-5/8" REG LH
Overall Dimension (L xW x H)	mm(in)	2505 x 758 x840 (98 <sup>5</sup> / <sub>8</sub> x 29 <sup>7</sup> / <sub>8</sub> x 33)	2786 x 706 x 791 (109 <sup>5</sup> / <sub>8</sub> x 27 <sup>3</sup> / <sub>4</sub> x 31)	2880 x 1046 x 1065 ( 113 <sup>5</sup> / <sub>8</sub> x 41 <sup>1</sup> / <sub>8</sub> x 42)	3015 x 1096 x 1065 (118 <sup>3</sup> / <sub>4</sub> x 43 <sup>1</sup> / <sub>8</sub> x 42)	3115 x 1143 x 990 (122 <sup>5</sup> / <sub>8</sub> x 45 x 39)
Weight	kg(lbs)	1341 (2956)	1834(4043)	2570 (5665)	3060 (6746)	4000(8818.5)

Note: The above-mentioned swivels have two options, equipped with spinners or without spinners.

Модель		SL135	SL180	SL225	SL450	SL675
Параметры						
Макс. номн. нагрузка на крюке	кН(ton )	1350(135)	1800(180)	2250(225)	4500(450)	6750(675)
Макс. скорость вращения	об/мин (rpm)	300				
Макс. рабочее давление	МПа (psi)	35 (5000)				52(7500)
Зазор крюка	мм	495	540	540	549	584
Диаметр центральной трубы	мм(in)	64(2-1/2) 64(2-1/2)		75(3) 75(3)		102(4)
Резьба соединения	To Stem	4-1/2"REG LH	6-5/8"REG LH		7-5/8" REG LH	
	To Kelly	6-5/8" REG LH				
Габариты (Д xШ x В)	мм	2505 x 758 x840	2786 x 706 x 791	2880 x 1046 x 1065	3015 x 1096 x 1065	3115 x 1143 x 990
Вес	кг	1341	1834	2570	3060	4000
Замечание: вышеуказанный вертлюг разделен на 2 вида: с закруткой и без закрутки						