

型号		TC135	TC180	TC225	TC315	TC450	TC675
参数							
最大钩载	kN(ton)	1350(135)	1800(180)	2250(225)	3150(315)	4500(450)	6750(675)
滑轮外径	MM	915	1005	1120	1270	1524	1524
滑轮数	шт	5	6	6	7	7	8
钢丝绳直径	MM(in)	29(1-1/8)	29(1-1/8)	32(1-1/4)	35(1-3/8)	38(1-1/2)	45(1-3/4)
外径尺寸 (长 X 宽 X 高)	MM	2500x2050x1920	2690 x 2150 x 2050	3200 x 3346 x 3640	3295 x 2622 x 3712	3460 x 2794 x 3772	3750 x 3760 x 3700
重量	kg	2400	2920	5310	7944	11230	12000

可根据天车的特殊要求设计制造。

Model		TC135	TC170	TC225	TC315	TC450	TC675
Specifications							
Max. Hook Load	kN(lbs)	1350 (300,000)	1700 (350,000)	2250 (500,000)	3150 (700,000)	4500 (1,000,000)	6750 (1,500,000)
O.D. of Sheaves	mm(in)	915 (36)	1005 (40)	1120 (44)	1270 (60)	1524 (60)	1524 (60)
Number of Sheaves		5	6	6	7	7	8
Dia. of Wire Line	mm(in)	29 (1 <sup>1</sup> / <sub>8</sub> )	29 (1 <sup>1</sup> / <sub>8</sub> )	32 (1 <sup>1</sup> / <sub>4</sub> )	35 (1 <sup>3</sup> / <sub>8</sub> )	38 (1 <sup>1</sup> / <sub>2</sub> )	45 (1 <sup>3</sup> / <sub>4</sub> )
Overall Dimension (L x W x H)	mm(in)	2500x2050x1920 (98 <sup>1</sup> / <sub>2</sub> x 80 <sup>3</sup> / <sub>4</sub> x 75 <sup>5</sup> / <sub>8</sub> )	2690 x 2150 x 2050 (105 <sup>7</sup> / <sub>8</sub> x 84 <sup>5</sup> / <sub>8</sub> x 80 <sup>3</sup> / <sub>4</sub> )	3200 x 3346 x 3640 (125 <sup>3</sup> / <sub>4</sub> x 131 <sup>3</sup> / <sub>4</sub> x 143 <sup>1</sup> / <sub>4</sub> )	3295 x 2622 x 3712 (129 <sup>3</sup> / <sub>4</sub> x 103 <sup>1</sup> / <sub>4</sub> x 146 <sup>1</sup> / <sub>8</sub> )	3460 x 2794 x 3772 (136 <sup>1</sup> / <sub>4</sub> x 110 x 148 <sup>1</sup> / <sub>2</sub> )	3750 x 3760 x 3700 (147 <sup>5</sup> / <sub>8</sub> x 148 x 145 <sup>5</sup> / <sub>8</sub> )
Weight	kg(lbs)	2400 (5290)	2920 (6440)	5310 (11700)	7944 (17510)	11230 (24760)	12000 (26455)

\*Special requirement for Crown Block is available for ZPEC to design and manufacture.

Модель		TC135	TC180	TC225	TC315	TC450	TC675
Параметры							
Макс.нагрузка на крюке	kH(ton)	1350(135)	1800(180)	2250(225)	3150(315)	4500(450)	6750(675)
Наружный диаметр шкива	MM	915	1005	1120	1270	1524	1524
Количество шкива		5	6	6	7	7	8
Диаметр каната	MM(in)	29(1-1/8)	29(1-1/8)	32(1-1/4)	35(1-3/8)	38(1-1/2)	45(1-3/4)
Габариты (Дx Ш x В)	MM	2500x2050	2690 x	3200 x	3295 x 2622	3460 x	3750 x

		0x 1920	2150 x 2050	3346 x 3640	x 3712	2794 x 3772	3760 x 3700
Вес	кг	2400	2920	5310	7944	11230	12000
<b>*Можно конструировать и изготовить согласно специальным требованиям к кронблоку.</b>							